

A close-up, black and white photograph of a tire tread pattern. The tread consists of several large, interlocking, block-like shapes arranged in a repeating pattern. Each block has a central longitudinal groove and is secured to the tire body with small screws. The lighting creates strong shadows, emphasizing the three-dimensional texture of the tread.

KENDA
TIRES

**ATV / UTV &
MOTORCYCLE
TIRES & TUBES**

2021



JACKSON STRONG GOES PYRO
FOR X-GAMES REAL MOTO 2020



KENDA

WELCOME TO KENDA

Where form and function transform into traction

«««KENDA

KENDA

Designed for Your Journey

ATV/UTV TIRES**ATV/UTV**

K3204R Klever X/T	12
K576A Kongur.....	12
K3201 Mastodon HT.....	12
K3203 Mastodon AT.....	14
K587 Bear Claw HTR	14
K299A Bear Claw XL.....	14
K299 Bear Claw.....	16
K592 Bear Claw EVO.....	16
K538 Executioner.....	18
K530 Pathfinder	18

ATV SPORT

K3210F/K3211 Havok.....	22
K580F/K581 Kutter MX	22
K580F/K581 Kutter XC.....	22
K300 Dominator	22
K532F/K533 Klaw MX	24
K532F/K533 Klaw XC.....	24
K284 Front Max.....	24
K290 Scorpion.....	24
K572 Road Go	26
K546/K547 Speed Racer..	26
K584 Snow Mad	26

TUBES

Motorcycle Tubes	60
ATV / UTV Tubes	62

MOTORCYCLE TIRES**OFF-ROAD**

K7102F Washougal III.....	30
K775F/K786 Washougal II	30
K785 Millville II	30
K780 Southwick II.....	32
K781 Triple	32
K772 Parker DT	32
K782 Sand Mad.....	34
K257D Klassic.....	34
K787 Equilibrium.....	34
K777F/K778 Knarly.....	36
K776F/K779 Gauntlet	36
K774 Ibex	36

DUAL SPORT/ADVENTURE

K784 Big Block	40
K678 Big Block Paver.....	40
K761 Dual Sport.....	40
K760 Trakmaster.....	42
K335 IceTire	42
K270 Dual Sport.....	42

STREET

KR20 Kanine	46
K6702 Cataclysm.....	46
K673 Kruz	46
K657 Challenger.....	48
K676 Retroactive	48
K671 Cruiser	48

SCOOTER

K784 Big Block	52
K262 Small Block.....	52
KD2 Kwick II.....	54
KD1 Kwick	54
K6022 Kozmik.....	54
K701 Winter.....	56
K329	56
K413	56
K433F/K434	58
K764	58
K453	58

TIRE SIDEWALL INFORMATION GUIDE

TECHNICAL



METRIC TIRE SIZING

150/80R-16 58W

Tire Width
Aspect Ratio
Structure Code
Rim Diameter
Load Index
Speed Rating

ALPHA TIRE SIZING

MV85-16 58W

Motorcycle Code
Tire Width
Aspect Ratio
Rim Diameter
Load Index
Speed Rating

STANDARD TIRE SIZING, INCHES

6.00-16 58W

Section Width
Rim Diameter
Load Index
Speed Rating

ATV TIRE SIZING, INCHES

24 X 8 - 12

Overall Diameter
Section Width
Rim Diameter

TIRE SIZE CONVERSION GUIDES

KENDA STREET MOTORCYCLE TIRE SIZE CONVERSION CHART

FRONT TIRES		
METRIC	ALPHA	INCH
80/90	MH90	2.50/2.75
90/90	MJ90	2.75/3.00
100/80	MJ90	3.00
100/90	MM90	3.25/3.5
110/70	*	*
110/80	*	3.25/3.5
110/90	MN90	3.75/4.00
120/70	*	*
120/80	*	3.75/4.25/4.60
120/90	MR90	4.25/4.50
130/60	*	*
130/70	*	*
130/90	MT90	5.00/5.10
REAR TIRES		
METRIC	ALPHA	INCH
110/90	MN90	3.75/4.25
120/80	MP85	4.50/4.75
120/90	MP85	4.50/4.75
130/70	*	*
130/80	*	5.00/5.10
130/90	MT90	5.00/5.10
140/60	*	*
140/70	*	*
140/80	*	5.50/6.00
140/90	MU90	5.50/6.00
150/70	*	*
150/80	MV85	6.00/6.25
150/90	MV85	6.00/6.25
160/60	*	*
160/70	*	*
160/80	*	*
170/60	*	*
170/80	*	*
180/50	*	*
180/55	*	*

*OEM low profile sizing

KENDA KNOBBY MOTORCYCLE TIRE SIZE CONVERSION CHART

FRONT TIRES	
METRIC	INCH
60/100	2.50/2.75
70/100	2.75/3
80/100	3/3.25
90/100	3.25
REAR TIRES	
METRIC	INCH
80/100	2.5/3.00
-	3.25/3.50
-	3.25/3.50
90/100	3.60/4.10
100/100	4.00/4.50
110/100	4.00/4.50
-	4.00/4.50
120/100	5.00/5.10
-	5.00/5.50
-	5.50

LOAD INDEX

L.I.	L.B.	L.I.	L.B.	L.I.	L.B.
33	254	50	419	67	677
34	260	51	430	68	694
35	267	52	441	69	716
36	276	53	454	70	739
37	282	54	467	71	761
38	291	55	481	72	783
39	300	56	494	73	805
40	309	57	507	74	827
41	320	58	520	75	853
42	331	59	536	76	882
43	342	60	551	77	908
44	353	61	567	78	937
45	364	62	584	79	963
46	375	63	600	80	992
47	386	64	617	81	1019
48	397	65	639	82	1047
49	408	66	661	83	1074

TECHNICAL

SPEED RATINGS

RATING	F	J	K	L	M	N	P	Q	R	S	T	U	H	V	Z	W	Y
MAX MPH	50	62	68	74	81	87	94	100	106	112	118	124	130	149	149+	168	186





JEFF WARD #3x

LEGENDS RIDE KENDA

JEFF WARD

7-time international MX des Nations Champion. X Games gold medalist. Multi-time AMA Motocross, Supercross, Supermoto champion. AMA Motorcycle Hall of Fame inductee. Jeff 'Wardy' Ward becomes the newest member of the Kenda Legends team, representing Kenda tires in multiple disciplines including Automotive, Motorcycle and Bicycle. Join Kenda in welcoming Jeff to the team.

#RideKenda

KENDA
Designed for Your Journey



DOUG HENRY #19



LEGENDS RIDE KENDA

DOUG HENRY

AMA Hall of Famer Doug Henry continues as part of the Kenda team for his second year.

Doug continues to dominate in adaptive racing events including motocross and downhill mountain biking on his Kenda tires while being an inspiration to other athletes across the board.

[#RideKenda](#)

KENDA
Designed for Your Journey



ATV/UTV





ATV | UTV



KLEVER X/T K3204R

- Lightest steel-belted 8-ply rated UTV tire on the market
- Studdable design for winter duty in snow and ice
- Smooth ride quality, low rolling resistance, and exceptional traction on all surfaces
- Robust bead protector shields wheels from trail debris and rocks
- DOT approved for road use



KONGUR K576A

- Ultimate trail and hard terrain UTV/SXS tire
- Radial design enables a smooth quality ride
- Light truck inspired tread pattern
- 8-ply rated, heavy-duty radial
- Meets or exceeds DOT standards (FMVSS S71.119)



MASTODON HT K3201

- BAJA 1000 winner
- Hard-Terrain (HT) is the ultimate trail and hard terrain UTV/SXS tire
- Smooth ride quality with light truck tire influenced tread pattern
- Built to excel in both high-speed desert conditions and tight, rocky terrain
- 8-ply rated, heavy-duty radial
- Meets or exceeds DOT standards (FMVSS S71.119)

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K3204R KLEVER XT													
083204141D1	FRONT	27X9.00R14	8PR	65M	27	9	636	38	17	31	14X7.0AT	TL	Y
083204142D1	REAR	27X11.00R14	8PR	71M	27	11	770	38	17	33	14X8.0AT	TL	Y
083204143D1	F/R	28X10.00R14	8PR	70M	28	10	744	38	17	35	14X8.0AT	TL	Y
083204144D1	F/R	30X10.00R14	8PR	74M	30	10	845	38	17	37	14X8.0AT	TL	Y
083204145D1	F/R	32X10.00R14	8PR	79M	32	10	957	38	17	39	14X8.0AT	TL	Y
083204151D1	F/R	32X10.00R15	8PR	78M	32	10	938	38	17	39	14X8.0AT	TL	Y
K576A KONGUR													
085761401D1	F/R	28X10.00R14	8PR	59M	29	10	536	22	11	34	14X7.0AT	TL	N
085761402D1	F/R	30X10.00R14	8PR	63M	31	11	600	22	11	39	14X7.0AT	TL	N
K3201 MASTODON HT													
0832011201D1	FRONT	25X8.00R12	8PR	43N	26	8	342	24	18	23	12X7.0AT	TL	N
0832011203D1	REAR	25X10.00R12	8PR	50N	26	10	419	24	18	27	12X8.0AT	TL	N
0832011202D1	FRONT	26X9.00R12	8PR	49N	27	9	408	24	20	28	12X7.0AT	TL	N
0832011204D1	REAR	26X11.00R12	8PR	55N	27	11	480	24	20	31	12X8.0AT	TL	N
0832011205D1	FRONT	27x9.00R12	8PR	66M	27	9	661	38	20	28	12X7.0AT	TL	N
0832011206D1	REAR	27x11.00R12	8PR	71M	27	10	760	38	20	31	12x9.0AT	TL	N
0832011401D1	FRONT	26X9.00R14	8PR	48N	27	9	397	24	20	28	14X7.0AT	TL	N
0832011404D1	REAR	26X11.00R14	8PR	56N	27	11	494	26	20	32	14X8.0AT	TL	N
0832011405D1	FRONT	28X9.00R14	8PR	67M	28	9	676	38	20	31	14X7.0AT	TL	N
0832011402D1	F/R	28X10.00R14	8PR	59M	29	10	536	22	20	32	14X8.0AT	TL	N
0832011406D1	REAR	28X11.00R14	8PR	73M	28	10	804	38	20	33	14x9.0AT	TL	N
0832011403D1	F/R	30X10.00R14	8PR	63M	31	10	600	22	20	35	14X8.0AT	TL	N
0832011407D1	F/R	32X10.00R14	8PR	78M	32	10	937	38	20	40	14X8.0AT	TL	N
0832011501D1	F/R	30X10.00R15	8PR	73M	30	10	804	38	20	37	15X8.0AT	TL	N
0832011502D1	F/R	32X10.00R15	8PR	77M	32	10	908	38	20	41	15X8.0AT	TL	N
0832011503D1	F/R	33X10.00R15	8PR	80M	33	10	992	38	20	42	15X8.0AT	TL	N
0832011504D1	F/R	35X10.00R15	8PR	84M	35	10	1102	38	20	45	15X8.0AT	TL	N





ATV | UTV



MASTODON AT K3203

- All-Terrain (AT) is the ultimate “do-it-all” UTV/SXS tire
- Aggressive, open tread design for good clean out performance in mud
- Large contact patch on harder ground conditions for superior traction and durability
- 8-ply rated, heavy-duty radial
- Meets or exceeds DOT standards (FMVSS 571.119)



BEAR CLAW HTR K587

- Tread pattern provides high traction on a wide range of terrain
- Center knob design provides low vibration and a smooth ride
- Self-cleaning design
- 8-ply rated, heavy-duty radial



BEAR CLAW XL K299A

- Classic design now with deeper tread for soft and muddy terrains
- Angled knobs dig into the terrain for maximum traction
- Center lugs provide extra traction and better control
- Deeper rim guard protects your wheel from dings/dents
- Long-range tread compound
- 6-ply rated casing allows for exceptional puncture resistance while keeping weight to a minimum

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K3203 MASTODON AT													
0832031201D1	FRONT	25X8.00R12	8PR	43N	26	8	342	24	18	23	12X7.0AT	TL	N
0832031203D1	REAR	25X10.00R12	8PR	50N	26	10	419	24	18	27	12X8.0AT	TL	N
0832031202D1	FRONT	26X9.00R12	8PR	49N	27	9	408	24	20	28	12X7.0AT	TL	N
0832031204D1	REAR	26X11.00R12	8PR	55N	27	11	480	24	20	31	12X8.0AT	TL	N
0832031205D1	FRONT	27x9.00R12	8PR	66M	27	9	661	38	20	28	12X7.0AT	TL	N
0832031206D1	REAR	27x11.00R12	8PR	71M	27	10	760	38	20	31	12x9.0AT	TL	N
0832031401D1	FRONT	26X9.00R14	8PR	48N	27	9	397	24	20	28	14X7.0AT	TL	N
0832031404D1	REAR	26X11.00R14	8PR	56N	27	11	494	26	20	32	14X8.0AT	TL	N
0832031405D1	FRONT	28X9.00R14	8PR	67M	28	9	676	38	20	31	14X7.0AT	TL	N
0832031402D1	F/R	28X10.00R14	8PR	59M	29	10	536	22	20	32	14X8.0AT	TL	N
0832031406D1	REAR	28X11.00R14	8PR	73M	28	10	804	38	20	33	14x9.0AT	TL	N
0832031403D1	F/R	30X10.00R14	8PR	63M	31	10	600	22	20	35	14X8.0AT	TL	N
0832031407D1	F/R	32X10.00R14	8PR	78M	332	10	937	38	20	40	14X8.0AT	TL	N
0832031501D1	F/R	30X10.00R15	8PR	73M	30	10	804	38	20	37	15X8.0AT	TL	N
0832031502D1	F/R	32X10.00R15	8PR	77M	32	10	908	38	20	41	15X8.0AT	TL	N
0832031503D1	F/R	33X10.00R15	8PR	80M	33	10	992	38	20	42	15X8.0AT	TL	N
0832031504D1	F/R	35X10.00R15	8PR	84M	35	10	1102	38	20	45	15X8.0AT	TL	N
K587 BEAR CLAW HTR													
085871245D1	FRONT	25X8.00R12	8PR	43N	25.40	8.20	340	7	21	21	12X7.0AT	TL	N
085871295D1	REAR	25X10.00R12	8PR	50N	25.40	10.00	420	7	21	25	12X8.0AT	TL	N
085871269D1	FRONT	26X9.00R12	8PR	49N	26.40	9.10	408	7	21	25	12X7.0AT	TL	N
085871261D1	REAR	26X11.00R12	8PR	55N	26.50	11.10	481	7	21	31	12X8.0AT	TL	N
085871258D1	FRONT	27X9.00R12	8PR	52N	27.20	9.20	440	7	21	25	12X7.0AT	TL	N
085871271D1	REAR	27X11.00R12	8PR	56N	27.40	11.00	494	7	21	31	12X8.0AT	TL	N
085871469D1	FRONT	26X9.00R14	8PR	48N	26.40	9.30	396	7	21	26	14X7.0AT	TL	N
085871461D1	REAR	26X11.00R14	8PR	54N	26.40	10.90	465	7	21	30	14X8.0AT	TL	N
085871462D1	F/R	27X9.50R14	8 PR	52F	27	10	520	7	21	28	14X7.0AT	TL	N
085871465D1	FRONT	28X9.00R14	8PR	51L	28.10	8.66	430	7	21	26	14X7.0AT	TL	N
085871467D1	REAR	28X11.00R14	8PR	58L	28.10	10.40	520	7	21	34	14X8.0AT	TL	N
K299A BEAR CLAW XL													
082991114C1	REAR	24X10.00-11	6PR	48F	24	10	395	7	24	20	11x7.5AT	TL	N
082991216C1	REAR	24X8.00-12	6PR	35F	24	8	310	7	20	18	12X6.5AT	TL	N
082991246C1	FRONT	25X8.00-12	6PR	38F	25	8	340	7	20	19	12X6.5AT	TL	N
082991247C1	FRONT	25X10.00-12	6PR	45F	25	10	420	7	20	23	12X8.0AT	TL	N
082991280C1	FRONT	25X12.50-12	6PR	51F	25	12	495	7	20	30	12X9.5AT	TL	N
082991291C1	F/R	27X9.00-12	6PR	52F	27	9	440	7	32	26	12X7.0AT	TL	N



KENDA
BEAR CLAW

ATV | UTV



BEAR CLAW K299

- Angled knobs dig into the terrain for maximum traction
- Center lugs provide extra traction and better control
- Built-in rim guard protects your wheel from dings/dents
- Long-range tread compound
- 6-ply rated extra tough casing resists punctures

KENDA
BEAR CLAW



BEAR CLAW EVO K592

- Engineered with a focus on reducing weight without sacrificing durability
- Tread pattern designed to perform exceptionally across all terrains
- Large center knobs for improved straight line and braking traction
- Recessed-dimpled knobs for improved wet traction
- Uniquely shaped transition knobs for improved cornering traction & handling
- 6-ply rated casing allows for exceptional puncture resistance while keeping weight to a minimum

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K299 BEAR CLAW													
082990881C1	REAR	22X12.00-8	6PR	46F	21	11	430	7	20	25	8X9.5AT	TL	N
082990981C1	REAR	22X12.00-9	6PR	51F	22	11	430	7	20	23	9X9.5AT	TL	N
082990979C1	REAR	25X12.50-9	6PR	56F	25	11	495	7	20	29	9X9.5AT	TL	N
082991083C1	FRONT	22X8.00-10	6PR	36F	22	9	275	7	15	17	10X6.0AT	TL	N
082991081C1	REAR	22X12.00-10	6PR	51F	21	11	430	7	20	24	10X6.0AT	TL	N
082991040C1	FRONT	23X7.00-10	6PR	45F	22	7	275	7	20	15	10X5.5AT	TL	N
082991011C1	REAR	23X10.00-10	6PR	46F	23	10	374	7	15	19	10x8.0AT	TL	N
082991089C1	REAR	24X11.00-10	6PR	52F	23	11	440	7	15	20	10X9.0AT	TL	N
082991079C1	REAR	25X12.50-10	6PR	56F	24	12	495	7	20	25	10X9.5AT	TL	N
082991073C1	F/R	22X7.00-11	6PR	32F	22	7	255	7	15	13	11X5.5AT	TL	N
082991185C1	FRONT	23X8.00-11	6PR	38F	23	8	290	7	15	17	11X6.5AT	TL	N
082991191C1	FRONT	24X9.00-11	6PR	45F	24	9	365	7	15	21	11X7.0AT	TL	N
082991113C1	REAR	24X10.00-11	6PR	48F	24	9	395	7	15	19	11X7.5AT	TL	N
082991145C1	FRONT	25X8.00-11	6PR	50F	25	8	340	7	20	18	11X6.5AT	TL	N
082991195C1	REAR	25X10.00-11	6PR	50F	24	10	420	7	20	19	11X8.0AT	TL	N
082991179C1	REAR	25X12.50-11	6PR	56F	24	12	495	7	20	29	11X9.5AT	TL	N
082991215C1	FRONT	24X8.00-12	6PR	56F	23	8	493	10	15	14	12X6.5AT	TL	N
082991245C1	FRONT	25X8.00-12	6PR	43N	24	8	340	7	15	17	12X6.5AT	TL	N
082991292C1	REAR	25X10.00-12	6PR	50N	25	9	420	7	15	20	12X8.0AT	TL	N
082991279C1	REAR	25X12.50-12	6PR	56F	25	11	495	7	15	26	12X9.5AT	TL	N
082991248C1	FRONT	26X9.00-12	6PR	50N	26	9	420	7	15	18	12X7.0AT	TL	N
082991261C1	REAR	26X11.00-12	6PR	55N	26	11	418	7	15	28	12X9.0AT	TL	N
082991299C1	F/R	26X12.00-12	6PR	58L	25	12	520	7	15	26	12X10.5AT	TL	N
082991258C1	FRONT	27X9.00-12	6PR	52N	27	9	440	7	20	23	12X7.0AT	TL	N
082991298C1	F/R	27X10.00-12	6PR	54N	26	10	465	7	15	22	12X8.5AT	TL	N
082991271C1	REAR	27X11.00-12	6PR	56N	27	11	494	7	15	28	12x9.0AT	TL	N
082991294C1	F/R	27X12.00-12	6PR	60L	26	12	550	7	21	30	12X10.5AT	TL	N
K592 BEAR CLAW EVO													
085921245C1	FRONT	25X8.00-12	6PR	43N	25	8	340	7	15	17	12X7.0AT	TL	N
085921292C1	REAR	25X10.00-12	6PR	50N	25	10	420	7	15	21	12X8.0AT	TL	N
085921248C1	FRONT	26X9.00-12	6PR	49N	26	9	408	7	19	22	12X7.0AT	TL	N
085921261C1	REAR	26X11.00-12	6PR	55N	26	11	481	7	19	28	12X8.0AT	TL	N
085921258C1	FRONT	27X9.00-12	6PR	52N	27	9	440	7	20	24	12X7.0AT	TL	N
085921271C1	REAR	27X11.00-12	6PR	56N	27	11	494	7	20	30	12X8.0AT	TL	N
085921448C1	FRONT	26X9.00-14	6PR	48N	26	9	396	7	19	23	14X7.0AT	TL	N
085921461C1	REAR	26X11.00-14	6PR	54N	26	11	465	7	19	23	14X8.0AT	TL	N
085921465C1	FRONT	28X9.00-14	6PR	51L	28	9	430	7	20	24	14X7.0AT	TL	N
085921446C1	REAR	28X11.00-14	6PR	58L	28	10	520	7	20	26	14X8.0AT	TL	N





EXECUTIONER K538

- Designed for deep down traction, even in the muddiest conditions
- Reinforced knobs reduce roll at low pressure, improve ride comfort and increase tread life
- Dimpled tread surface for improved traction on drier conditions
- Deep rim guard feature for protection against rock and rut damage
- 6-ply rated with extra tough casing resists punctures



PATHFINDER K530F/K530

- Ideal choice for riders seeking the best value all-terrain option
- Tread designed for smooth and dependable ride performance

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K538 EXECUTIONER													
085381245C1	FRONT	25X8.00-12	6PR	43L	8.30	24.80	340	7	21.50	21	12X7.0AT	TL	N
085381225C1	REAR	25X10.00-12	6PR	50L	9.60	24.80	420	7	26.50	28	12X8.0AT	TL	N
085381298C1	FRONT	26X10.00-12	6PR	52L	9.50	26.00	440	7	26.50	29	12X8.0AT	TL	N
085381299C1	REAR	26X12.00-12	6PR	58L	12.00	26.00	520	7	26.50	34	12X9.5AT	TL	N
085381298C1	FRONT	27X10.00-12	6PR	54F	9.80	27.10	465	7	29.50	32	12*7.0	TL	N
08538129AC1	REAR	27X12.00-12	6PR	60F	11.30	27.20	550	7	29.50	35	12*8.5	TL	N
085381465C1	FRONT	28X9.00-14	6PR	51L	8.50	28.00	430	7	29.50	28	14X7.0AT	TL	N
085381467C1	REAR	28X11.00-14	6PR	58L	10.40	27.90	520	7	29.50	32	14X8.0AT	TL	N
K530 PATHFINDER													
085300762A1	FRONT	16X8.00-7	2PR	28F	7.40	15.60	220	5	9.50	8.11	7x6.5AT	TL	N
085400764B1	FRONT	18X7.00-7	2PR	23F	6.90	17.20	195	5	9.50	7.64	7x6.5AT	TL	N
085300870A1	REAR	18X9.50-8	2PR	30F	9.20	18.10	233	5	12.50	10.37	8X7.0AT	TL	N
085300840A1	FRONT	19X7.00-8	2PR	30F	7.00	18.80	233	5	9.50	8.65	8X6.0AT	TL	N
085300884A1	REAR	22X11.00-8	2PR	43F	10.80	22.00	275	5	12.50	17.81	8X9.0AT	TL	N
085300984A1	REAR	22X11.00-9	2PR	43F	10.90	22.00	275	5	12.50	17.13	9X9.0AT	TL	N
085300992A1	REAR	25X12.00-9	2PR	51F	11.40	24.50	355	5	13.50	22.07	9X9.5AT	TL	N
085301084A1	REAR	22X11.00-10	2PR	42F	10.50	21.10	265	5	12.50	17.04	10X9.0AT	TL	N
085301092A1	REAR	25X12.00-10	2PR	51F	10.90	23.70	355	5	14.00	19.90	10X9.5AT	TL	N
085401185A1	FRONT	23X8.00-11	4PR	33F	8.10	23.10	255	5	12.50	13.10	11X6.5AT	TL	N
085301191A1	REAR	24X9.00-11	4PR	33F	9.00	23.70	255	5	12.50	15.02	11X7.0AT	TL	N
085301245A1	FRONT	24X8.00-12	2PR	35F	7.70	23.20	220	5	12.50	12.88	12X6.5AT	TL	N
08530F1245B1	FRONT	25X8.00-12	4PR	38N	7.80	25.00	290	5	12.50	17.01	12X6.5AT	TL	N
085301295B1	REAR	25X10.00-12	4PR	45N	9.40	25.00	365	5	14.50	18.66	12X8.0AT	TL	N





SPORT ATV



HAVOK
KENDA

ATV | SPORT



HAVOK K3210F/K3211

- Optimized tread spacing designed for all sport and race ATV applications
- Unique race compound delivers superior traction while extending tread life
- Laboratory-tested and competition-proven in the most demanding conditions
- Non-directional 6-ply-rated carcass
- All-new profile for predictable steering, braking and acceleration

KENDA
KUTTER



KUTTER MX, XC K580F/K581

KUTTER MX

- Tread pattern provides more biting edges for improved traction
- Sticky rubber compound for the ultimate in traction
- Lightweight 4-ply casing structure with reinforced sidewalls
- Flatter profile for more contact with the ground

KUTTER XC

- Designed to meet the demands of the toughest off-road terrain
- Large durable knob shapes to provide extra traction and long life
- Large footprint for extra traction
- Heavy duty 6-ply rated casing perfected to handle tough terrain


KENDA
DOMINATOR



DOMINATOR K300

- Professional technology designed for the recreational rider
- Split knob design for exceptional cornering and braking

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K3210F/K3211 HAVOK													
083210108C1	FRONT	21X7-10	6PR	43N	21	7	235	7	14	11	10X5.5	TL	N
083211104C1	REAR	20X11-9	6PR	30N	20	11	340	7	13	15	9X9.0	TL	N
083210206FB1	FRONT	A120X6-10	4PR	17F	20	6	160	5	12	9	10x5.5	TL	N
0832111802B1	REAR	A118X10-8	4PR	25J	18	10	210	5	12	12	8x8.5	TL	N
0832111810B1	REAR	18x10.00-9	4PR	32J	18	10	245	7	12	12	9x8	TL	N
0832111801B1	REAR	18x8.00-8	4PR	26N	18	8	210	7	12	11	8x7	TL	N
083210237FC1	FRONT	23x7.00-10	4PR	36J	23	7	275	8	13	12	10x5.5	TL	N
083211221C1	REAR	22x11.00-9	4PR	48J	22	11	395	8	14	15	9x9	TL	N
K580 KUTTER MX/XC, FRONT													
085801021B1	FRONT	19X6.00-10	6PR	19N	19	6	168	7	12	10	10X5.0AT	TL	N
085801080B1	FRONT	20X6.00-10	4PR	17J	20	7	161	5	10	9	10X5.5AT	TL	N
085801080C1	FRONT	21X7.00-10	6PR	30N	21	7	235	7	15	13	10X5.5AT	TL	N
085801005C1	FRONT	22X7.00-10	6PR	33N	22	7	255	7	15	14	10X5.5AT	TL	N
K581 KUTTER MX/XC, REAR													
085810868B1	REAR	18X8.00-8	6PR	26N	18	8	210	7	12	12	8X7.0AT	TL	N
085810809B1	REAR	18X10.00-8	4PR	29J	18	10	255	5	12	10	8X8.5AT	TL	N
085810909B1	REAR	18X10.00-9	4PR	32J	18	10	245	7	12	13	9X8.0AT	TL	N
085800946C1	REAR	20X11.00-9	6PR	40N	22	9	308	7	15	16	11X7.0AT	TL	N
08581171C1	REAR	22X9.00-11	6PR	40N	22	9	308	7	15	16	11X7.0AT	TL	N
K300 DOMINATOR													
083000874B1	FRONT	20X7.00-8	4PR	23F	20	7	195	5	12	10	8X5.5AT	TL	N
083000846B1	REAR	20X11.00-8	4PR	38F	20	11	290	5	12	14	8X9.0AT	TL	N
083000884B1	REAR	22X11.00-8	4PR	43F	22	11	340	5	13	17	8X9.0AT	TL	N
083000973B1	REAR	20X11.00-9	4PR	38F	20	11	290	5	12	14	9X9.0AT	TL	N
083000984B1	REAR	22X11.00-9	4PR	43F	21	11	340	5	13	15	9X9.0AT	TL	N
083001080B1	FRONT	21X7.00-10	4PR	25F	21	7	205	5	12	10	10X5.5AT	TL	N
083001083B1	FRONT	22X8.00-10	4PR	31F	22	8	240	5	12	13	10X6.0AT	TL	N
083001073B1	REAR	20X11.00-10	4PR	37F	20	11	280	5	12	16	10X9.0AT	TL	N
083001084B1	REAR	22X11.00-10	4PR	42F	22	11	330	5	12	18	10X9.0AT	TL	N



KENDA
KLAW

ATV | SPORT



KLAW MX, XC K532F/533

KLAW MX

- Reversible rotation direction for either soft or hard terrain
- Lightweight 4-ply rated casing reduces unsprung weight

KLAW XC

- 6-ply rated casing
- Meets the demands of the toughest cross country terrain
- Performs in a mix of terrains ranging from cross country to short course racing
- Reversible rotation direction for either soft or hard terrain



FRONT MAX K284

- First front rib tire designed exclusively for ATV use
- Reinforced knobs for superior tracking and cornering
- One of the best and most popular replacement tires on the market
- Puncture resistant casing


KENDA
SCORPION



SCORPION K290

- Provides versatility for a mix of terrains and applications
- Ideal choice for riders seeking all-terrain performance at a low price
- Lightweight, easy rolling design
- Puncture resistant
- Good rear match for our K284 Front Max

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K532 KLAW MX/XC, FRONT													
085321032B1	FRONT	20X6.00-10	4PR	17F	19	7	160	5	10	9	10X5.5AT	TL	N
085321080C1	FRONT	21X7.00-10	6PR	30N	21	7	235	7	10	9	10X5.5AT	TL	N
085321005C1	FRONT	22X7.00-10	6PR	33F	22	7	255	7	12	12	10*5.5	TL	N
085321040C1	FRONT	23X7.00-10	6PR	35F	23	7	275	7	15	13	10x5.5AT	TL	N
085321245C1	FRONT	25X8.00-12	6PR	38F	25	8	340	7	14	16	12X6.5AT	TL	N
K533 KLAW MX/XC, REAR													
085330809B1	REAR	18X10.50-8	4PR	29F	18.20	10.20	225	5	13	13	8X8.5AT	TL	N
085330909B1	REAR	18X10.50-9	4PR	32F	18.00	10.40	245	7	13	13	9X9.0AT	TL	N
085330849C1	REAR	20X11.00-8	6PR	38F	20.70	11.40	340	7	13	16	8X9.0AT	TL	N
085330884C1	REAR	22X11.00-8	6PR	43F	22.60	11.50	395	7	13	21	8X9.0AT	TL	N
085330973C1	REAR	20X11.00-9	6PR	43F	20.60	10.60	340	7	13	16	9X9.0AT	TL	N
085330984C1	REAR	22X11.00-9	6PR	43F	22.60	11.10	395	7	13	19	9X9.0AT	TL	N
085331073C1	REAR	20X11.00-10	6PR	42F	20.80	10.20	330	7	13	18	10X9.0AT	TL	N
085321005C1	REAR	22X11.00-10	6PR	47F	22.80	10.90	385	7	13	19	10X9.0AT	TL	N
085331292C1	REAR	25X10.00-12	6PR	50N	25.20	9.90	420	7	13	20	12X8.0AT	TL	N
K284 FRONT MAX													
082840874A1	FRONT	20X7.00-8	2PR	23F	21	7	195	5	13	15	8X5.5AT	TL	N
082840884A1	FRONT	22X11.00-8	2PR	43F	22	10	340	5	15	17	8X9.0AT	TL	N
082840982A1	FRONT	21X8.00-9	2PR	29F	21	7	225	5	13	12	9X6.5AT	TL	N
082841080A1	FRONT	21X7.00-10	2PR	25F	21	7	205	5	13	12	10X5.5AT	TL	N
082841083A1	FRONT	22X8.00-10	2PR	31F	21	7	240	5	13	11	10x5.5AT	TL	N
082841084A1	FRONT	22X11.00-10	2PR	42F	23	10	330	5	13	17	10X9.0AT	TL	N
082841185A1	FRONT	23X8.00-11	2PR	33F	23	8	255	10	13	16	11X6.5AT	TL	N
082841190A1	FRONT	23.5X8.00-11	2PR	33F	23	8	255	10	13	16	11X6.5AT	TL	N
K290 SCORPION													
082900657A1	REAR	14.5X7.00-6	2PR	18F	14	5	165	5	5	4	6x4.5AT	TL	N
082900762A1	REAR	16X8.00-7	2PR	28F	15	8	220	5	7	7	7x6.5AT	TL	N
082900870A1	REAR	18X9.50-8	2PR	26F	18	9	233	5	10	11	8X7.0AT	TL	N
082900840A1	REAR	19X7.00-8	2PR	30F	19	7	233	5	10	9	8X5.5AT	TL	N
082900874A1	REAR	20X7.00-8	2PR	23F	19	7	195	5	10	10	8X5.5AT	TL	N
082900876A1	REAR	20X10.00-8	2PR	35F	20	9	265	5	12	13	8X8.0AT	TL	N
082900880A1	REAR	22X10.00-8	2PR	39F	22	10	265	5	13	16	8X8.0AT	TL	N
082900884A1	REAR	22X11.00-8	2PR	43F	22	10	340	5	13	19	8X9.0AT	TL	N
082900976A1	REAR	20X10.00-9	2PR	34F	20	9	260	5	12	12	9X8.0AT	TL	N
082900992A1	REAR	25X12.00-9	2PR	51F	24	11	430	5	14	20	9X9.5AT	TL	N
082901191A1	REAR	24X9.00-11	2PR	40F	26	9	310	10	14	19	11X7.0AT	TL	N



KENDA
SPEED RACER

ATV | SPORT



SPEEDRACER K546F/K547

- Excellent design for harder surface sport riding
- Low-void tread pattern for reduced road noise and improved traction
- Directional tread pattern



KENDA



ROAD GO K572

- Designed for harder surfaces
- Low-void tread pattern for reduced road noise and improved traction
- Low rolling resistance
- Quiet/supple riding tire



SNOW MAD K584

- Tread pattern and compound designed specifically for winter conditions
- Lightweight, flexible casing to allow tire growth at speed and cushion on bumps

PART #	FRONT/ REAR	SIZE	PLY RATING	LOAD/ SPEED	OD INCHES	SW INCHES	MAX LOAD LBS	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K546 SPEED RACER FRONT													
085460840B1	FRONT	19X7.00-8	4PR	20N	19	7	175	5	10	11	8X5.5AT	TL	N
085460874B1	FRONT	20X7.00-8	4PR	23N	20	7	195	5	10	13	8X5.5AT	TL	N
085461080B1	FRONT	21X7.00-10	4PR	25N	21	7	205	5	10	13	10X5.5AT	TL	N
085461245C1	FRONT	25X8.00-12	6PR	43N	25	8	340	7	10	19	12X6.5AT	TL	N
K547 SPEED RACER REAR													
085470870B1	REAR	18X9.50-8	4PR	30N	18	9	233	5	10	14	8X7.0AT	TL	N
085470841B1	REAR	19X8.00-8	4PR	24N	19	9	200	5	10	13	8X7.0AT	TL	N
085470881B1	REAR	21X10.00-8	4PR	37N	21	11	280	5	10	17	8X8.0AT	TL	N
085470878B1	REAR	22X10.00-8	4PR	39N	22	10	300	5	10	18	8X8.0AT	TL	N
085470993B1	REAR	20X11.00-9	4PR	38N	21	11	290	5	10	18	9X9.0AT	TL	N
085471009B1	REAR	18X10.00-10	4PR	34N	19	10	260	5	10	16	10x8.0AT	TL	N
085471078B1	REAR	22X10.00-10	4PR	55N	22	10	480	5	10	17	10x8.0AT	TL	N
085471295C1	REAR	25X10.00-12	6PR	50N	25	9	420	7	10	21	12X8.0AT	TL	N
K572 ROAD GO													
085720870B1	FRONT	18X9.50-8	4PR	30N	18	9	235	5	9	12	8X7.0AT	TL	N
085720840B1	REAR	19X7.00-8	4PR	20N	19	7	175	5	9	12	8X5.5AT	TL	N
085720881B1	REAR	21X10.00-8	4PR	37N	21	10	280	5	9	10	8X8.0AT	TL	N
085720946B1	REAR	20X11.00-9	4PR	38N	20	11	290	5	9	13	10X9.0AT	TL	N
085721080B1	FRONT	21X7.00-10	4PR	25N	21	7	205	5	9	15	10X5.5AT	TL	N
085721080B1	REAR	22X10.00-10	4PR	55N	22	10	480	5	9	11	10X5.5AT	TL	N
085721245B1	FRONT	25X8.00-12	4PR	38N	25	8	290	5	9	15	12X6.5AT	TL	N
085721295B1	REAR	25X10.00-12	4PR	45N	25	10	365	5	9	16	12X8.0AT	TL	N
K584 SNOW MAD													
045840807A1	REAR	22X10.00-8	2PR	39F	22	10	245	4	14	6	8X8.5AT	TL	N
085840978A1	REAR	22X10.00-9	2PR	39F	22	10	245	4	14	13	9X8.5	TL	N





OFF-ROAD



W3
KENDA WASHOUGAL III

OFF-ROAD



WASHOUGAL III K7102F

- First offroad tire with Kenda's Advanced Apex (AA) technology for increased lateral response and optimal carcass stiffness
- All new tread design allows for faster forward roll, increased side bite, and controlled flex without washing out
- Unique sipe and groove orientation allow for linear cornering characteristics and superb braking control
- Larger footprint for better grip
- Deepest front tread in the offroad lineup and still FIM-compliant

W2
KENDA WASHOUGAL II



WASHOUGAL II K775F/K786

- Multi-time National Off-Road Championship winner
- Dual-compound rear for durability and cornering traction
- Front: Single compound
- Youth sizes feature Sticky compound only
- DOT approved front tire (21" only)

M2
KENDA MILLVILLE II



MILLVILLE II K785

- Directional designed for soft or intermediate terrain, perfect for MX
- New compound formula for traction and durability
- Scoop-shaped blocks improve braking traction
- Improved cornering traction with more biting edges
- Tie bar knob support to reduce knob squirm and increase durability
- DOT approved front tire (21" only)

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K7102F WASHOUGAL III											
047102212FI	FRONT	80/100-21	51M	28	3	36	14	9	1.60x21	TT	Y
K775 WASHOUGAL II											
047751032COS2	FRONT	250-10	33J	15	3	20	8	3	1.40X10	TT	N
047751232COS2	FRONT	250-12	33J	17	3	20	8	4	1.40X12	TT	N
047751401COS2	FRONT	60/100-14	30M	19	3	20	10	4	1.40X14	TT	N
047751702COS2	FRONT	70/100-17	40M	23	3	20	10	5	1.40X17	TT	N
047751902COS2	FRONT	70/100-19	42M	25	3	20	10	6	1.40X19	TT	N
047752130COP	FRONT	80/100-21	51M	28	4	20	12	9	1.60X21	TT	Y
047752140COP	FRONT	90/100-21	57M	28	4	20	12	9	1.60X21	TT	Y
K786 WASHOUGAL II											
047861003COS2	REAR	80/100-10	42J	16	3	20	9	4	1.40X10	TT	N
047861230COS2	REAR	80/100-12	41M	18	4	20	13	5	1.60X12	TT	N
047861440COS2	REAR	90/100-14	49M	21	4	20	14	8	1.60X14	TT	N
047861640COS2	REAR	90/100-16	52M	23	4	20	14	8	1.85X16	TT	N
047861811CO	REAR	110/100-18	64M	26	5	20	16	13	2.15X18	TT	N
047861813CO	REAR	120/100-18	68M	27	5	20	16	14	2.50X18	TT	N
047861906CO	REAR	100/90-19	57M	27	5	20	16	12	1.85X19	TT	N
047861923CO	REAR	110/80-19	59M	27	5	20	16	12	2.15X19	TT	N
047861910CO	REAR	110/90-19	62M	27	5	20	16	13	2.15X19	TT	N
047861979CO	REAR	120/80-19	63M	27	5	20	16	12	2.15X19	TT	N
K785 MILLVILLE											
047851203B0	REAR	80/100-12	41M	18	4	20	13	5	1.60X12	TT	N
047851401B0	FRONT	60/100-14	30M	19	3	20	9	4	1.60X14	TT	N
047851404B0	REAR	90/100-14	49M	21	4	20	14	7	1.60X14	TT	N
047851604B0	REAR	90/100-16	52M	23	4	20	14	8	1.85X16	TT	N
047851702B0	FRONT	70/100-17	40M	23	3	20	10	5	1.40X17	TT	N
047851902B0	FRONT	70/100-19	42M	25	3	20	10	6	1.40X19	TT	N
047851811B0	REAR	110/100-18	64M	26	5	20	16	12	2.15X18	TT	N
047851813B0	REAR	120/100-18	68M	27	5	20	16	13	2.50X18	TT	N
047851906B0	REAR	100/90-19	57M	27	5	20	16	13	1.85X19	TT	N
047851923B0	REAR	110/80-19	59M	27	5	20	16	13	2.15X19	TT	N
047851910B0	REAR	110/90-19	62M	27	5	20	16	13	2.15X19	TT	N
047851975B0	REAR	120/80-19	63M	27	5	20	16	12	2.15X19	TT	N
047852130B0	FRONT	80/100-21	51M	28	4	20	12	9	1.60X21	TT	N
047852104B0	FRONT	90/100-21	57M	28	4	20	12	9	1.60X21	TT	N





OFF-ROAD



SOUTHWICK II K780

- Designed for loose sand and muddy conditions
- Front and rear tread patterns offer tall knob depths for deep bite
- Large radius support at knob base reduces knob roll
- Wide space between rows self-cleans tread even at slow speed
- Increased wear durability and quick warm-up
- Lightweight 4-ply rated casing structure with reinforced sidewalls
- DOT approved front tire (21" only)



TRIPLE K781

- Developed and tested for Arenacross and Supercross applications
- Low profile sidewall for improved cornering stability and traction
- Tread pattern designed for hard packed, slippery surfaces
- Dimpled knobs allow for quick tire warm up and extra traction
- Sticky rubber compound for high traction
- Lightweight 4-ply rated casing structure with reinforced sidewalls
- DOT approved front tire (21" only)



PARKER DT K772

- The ultimate tire for fast desert terrain
- Casing/compound designed for the toughest hard-packed terrain
- Natural rubber compound for extended tread wear and reduced knob chunking
- 6-Ply rated casing offers 30% more cut resistance
- DOT approved front and rear

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K780 SOUTHWICK											
047801807B0	REAR	100/100-18	59M	26	5	20	17	12	1.85X18	TT	N
047801811B0	REAR	110/100-18	64M	26	5	20	17	12	2.15X18	TT	N
047801905B0	REAR	100/90-19	57M	27	5	20	17	11	1.85X19	TT	N
047801903B0	REAR	110/90-19	62M	27	5	20	17	12	2.15X19	TT	N
047802103B0	FRONT	80/100-21	51M	28	4	20	12	9	1.60X21	TT	Y
K781 TRIPLE											
047811811B1	REAR	110/100-18	64M	26	5	20	15	12	2.15X18	TT	N
047811813B0	REAR	120/100-18	68M	27	5	20	15	14	2.50X18	TT	N
047811906B0	REAR	100/90-19	57M	27	5	20	15	14	1.85X19	TT	N
047811923B0	REAR	110/80-19	59M	27	5	20	15	12	2.15X19	TT	N
047811910B0	REAR	110/90-19	62M	27	5	20	15	14	2.15X19	TT	N
047811979B0	REAR	120/80-19	63M	27	5	20	15	12	2.15X19	TT	N
047812103B1	FRONT	80/100-21	51M	28	4	20	12	9	1.60X21	TT	Y
047812104B0	FRONT	90/100-21	57M	28	4	20	12	9	1.60X21	TT	Y
K772 PARKER DT											
047721811COP	REAR	110/100-18	64M	26	5	20	16	13	2.15X18	TT	N
047721813COP	REAR	120/100-18	68M	27	5	20	16	13	2.50X18	TT	N
047721910COP	REAR	110/90-19	62M	27	5	20	16	13	2.15X19	TT	N
047721991C1	REAR	120/90-19	66M	28	5	20	16	14	2.50X19	TT	N
04772103COP	FRONT	80/100-21	51M	28	4	20	12	9	1.60X21	TT	Y



KENDA
SAND MAD



OFF-ROAD

SAND MAD K782

- Designed specifically for deep mud or sandy MX course conditions
- Paddle shaped knobs create a large scoop for improved acceleration traction
- Unique shoulder knob design for predictable cornering traction
- Siped knob surface for quick tire warm up on cement start pads
- Sticky rubber compound for high traction on concrete start gates
- Lightweight 4-ply rated casing structure with reinforced sidewalls

KENDA
Klassic



KLASSIC K257D

- High quality, value tire sized for most modern and vintage MX and off-road motorcycles
- Aggressive four/five knob pattern provides traction in a variety of terrains
- Vintage style and design add period-correct look to old school off-road bikes
- DOT approved front and rear

KENDA

EQUILIBRIUM



EQUILIBRIUM K787

- The best qualities of a trials tire and off-road tire all in one product
- Trials inspired center tread design for the best possible traction
- Motocross-style shoulder knobs for aggressive cornering
- Super Sticky race compound for unbeatable grip in both wet and dry conditions
- Braking scoops in center area provide stopping power that a trials tire can't
- Ultra soft casing for maximum terrain adaptation
- DOT approved

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K782 SAND MAD											
047821905B1	REAR	100/90-19	57M	27	5	20	17	11	1.85X19	TT	N
047821910B0	REAR	110/90-19	62M	27	5	20	16	13	2.15X19	TT	N
04782181100	REAR	110/100-18	62M	26.5	4.9	20	17	12	2.15X18	TT	N
K257D KLASSIC											
042571452B0	REAR	410-14	47M	22	4	33	14	8	2.15X14	TT	N
042571636B0	FRONT	300-16	43M	23	3	33	10	6	1.85X16	TT	N
042571838B0	REAR	350-18	56P	25	4	33	14	9	2.15X18	TT	N
042571764C0	REAR	510-17	71P	26	5	40	16	14	3.00X17	TT	Y
042571852B0	REAR	410-18	58P	25	4	33	14	9	2.15X18	TT	Y
042571852C0	REAR	410-18	63M	25	4	40	14	10	2.15X18	TT	Y
042571860B0	REAR	460-18	63P	28	5	33	17	8	2.15X18	TT	Y
042571858C0	REAR	450-18	70M	27	5	40	17	14	2.15X18	TT	Y
042571864C0	REAR	510-18	74M	27	5	40	16	14	2.15X18	TT	Y
042571866C0	REAR	530-18	75M	28	5	40	16	16	2.50X18	TT	N
042571906C0	REAR	100/90-19	57M	27	5	33	16	12	2.50X19	TT	Y
042571910C0	REAR	110/90-19	68M	27	5	40	16	13	2.15X19	TT	Y
042572134C0	FRONT	300-21	57M	28	3	33	10	9	1.85X21	TT	Y
042572136B0	FRONT	300-21	51M	28	3	40	10	9	1.85X21	TT	Y
K787 EQUILIBRIUM											
047871858C0	REAR	450-18	70M	27	5	33	13	13	2.15X18	TT	Y
047871979C0	REAR	120/80-19	63M	27	5	20	13	12	2.15X19	TT	Y

OFF-ROAD





OFF-ROAD



KNARLY K777F/778

- Extreme enduro FIM-approved
- Super-soft and flexible for ultimate terrain compliance and grip
- Compound provides highest traction in both wet and dry conditions
- Reversible rear for variable terrain applications
- Available in super wide rear



GAUNTLET K776F/779F

- Hard enduro FIM-approved
- Perfect balance of sticky grip and long-lasting wear
- Open, aggressive pattern allows for excellent cleanout
- Low front profile provides the best feel and confidence when traction matters most
- Available in super wide rear



IBEX K774

- Designed for Endurocross and extreme enduro-type conditions
- Super-soft and flexible rubber compound and casing for maximum bump absorption and terrain compliance for obstacles like rock gardens and log crossings
- High wet-traction compound developed by top pro Endurocross riders
- Open, aggressive drive pattern for max grip and cleanout
- Shoulder knob pattern designed for large contact patch and support for soft compound during cornering

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K777F/K778 KNARLY											
04778182002	REAR	120/90-18	65R	27	5	33	13	11	2.15X8	TT	N
04778184002	REAR	140/80-18	70R	27	5	33	13	12	2.50X18	TT	N
04778193002	REAR	130/80-19	67R	27	5	33	13	11	2.50X18	TT	N
04777219002	FRONT	90/90-21	54R	28	4	33	13	9	1.60X21	TT	N
K776F/K779 GAUNTLET											
04779183002	REAR	130/80-18	66R	27	5	33	13	11	2.50X18	TT	N
04779184002	REAR	140/80-18	70R	27	5	33	13	12	2.50X18	TT	N
04776219001	FRONT	90/90-21	54R	28	4	33	11	9	1.60X21	TT	N
K774 IBEX											
047741441B1CEX	REAR	90/100-14	49M	22	4	20	14	7	1.60X14	TT	N
04771641B1CEX	REAR	90/100-16	52M	24	4	20	14	8	1.85X16	TT	N
047741864CEX	REAR	110/100-18	64M	26	5	20	16	13	2.15X18	TT	N
047741813CEX	REAR	120/100-18	64M	27	5	20	16	14	2.50X18	TT	N
047741913B1CEX	REAR	120/90-19	66M	28	5	20	16	13	2.50X19	TT	N
047742131CEX	FRONT	80/100-21	51M	28	4	20	11	9	1.60X21	TT	Y
047742140CEX	FRONT	90/100-21	57M	28	4	20	11	9	1.60X21	TT	N





DUAL SPORT



DUAL SPORT



BIG BLOCK K784

- Our most popular 50/50 tire provides high traction on a variety of terrain
- Large tread blocks for improved tread wear and high speed handling
- High impact, bias belted, casing structure providing a high level of puncture resistance
- Rubber compound designed specifically for wet-slick & dry-hard packed terrain
- Tubeless
- DOT and E-mark approved
(50% dirt/50% road)



BIG BLOCK PAVER

K678F/K678

- Designed for adventure riders with a high-performance on-road focus
- Front tread designed to minimize scalloping common on heavier adventure bikes while providing long wear and excellent grip in all conditions
- Rear tread designed for high mileage while deep grooving provides traction in off-highway conditions
- DOT approved, tubeless
(20% dirt/80% road)



K761 DUAL SPORT K761

- One of the world's most popular dual sport tread patterns
- Perfect for road-focused dual sport applications
- Trusted by several major manufacturers for performance and reliability
- Tubeless
- DOT approved
(30% dirt/70% road)

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K784 BIG BLOCK											
047841201B1	FRONT	120/70-12	51P	19	5	33	10	7	3.50X12	TL	Y
047841202B1	REAR	130/70-12	56P	19	5	33	10	9	3.50X12	TL	Y
047841601B1	REAR	140/90-16	77Q	26	6	42	11	16	3.50X16	TL	Y
047841777B0	REAR	130/80B17	65T	25	5	36	11	14	3.00X17	TL	Y
047841721B0	REAR	150/70B17	69Q	25	6	36	11	16	4.25X17	TL	Y
047841787B0	REAR	170/60B17	72Q	25	7	36	11	18	4.50X17	TL	Y
047841822B0	REAR	140/80B18	70R	27	6	36	11	15	3.50X18	TL	Y
047841821B0	REAR	150/70B18	70Q	26	6	36	11	16	4.25X18	TL	Y
047841905B0	FRONT	100/90B19	57S	26	4	36	9	11	2.50X19	TL	Y
047841923B0	FRONT	110/80B19	59Q	25	4	36	9	11	2.50X19	TL	Y
047841986B0	FRONT	120/70B19	60Q	26	5	36	9	12	3.50X19	TL	Y
047842108B0	FRONT	90/90B21	54T	27	4	36	9	11	2.15X21	TL	Y
K678 BIG BLOCK PAVER											
04678170101	REAR	130/80B17	65H	25	5	42	9	15	3.00X17	TL	Y
04678170201	REAR	150/70B17	69H	25	6	42	9	19	4.25X17	TL	Y
04678170301	REAR	170/60B17	72H	25	7	42	9	18	4.50X17	TL	Y
04678180101	REAR	140/80B18	70H	27	6	42	9	18	3.50X18	TL	Y
04678180201	REAR	150/70B18	70H	26	6	42	9	17	4.25C18	TL	Y
04678190101	FRONT	100/90B19	57H	26	4	42	5	11	2.15X19	TL	Y
04678190201	FRONT	110/80B19	59H	25	4	42	5	13	2.50X19	TL	Y
04678190301	FRONT	120/70B19	60H	26	5	42	5	12	3.50X19	TL	Y
04678210101	FRONT	90/90B21	54H	27	4	42	5	11	2.15X21	TL	Y
K761 DUAL SPORT											
047611012B1	F/R	120/90-10	57J	19	5	25	6	8	2.75X10	TL	Y
047611014B1	F/R	130/90-10	61J	19	5	25	6	9	3.00X10	TL	Y
047611222B1	F/R	110/70-12	47J	18	4	33	6	7	3.00X12	TL	Y
047611210B1	F/R	110/90-12	64J	20	4	36	6	8	2.50X12	TL	Y
047611286B1	F/R	120/70-12	51J	19	5	33	6	7	3.50X12	TL	Y
047611279B1	F/R	120/80-12	65J	20	5	36	6	9	2.75X12	TL	Y
047611209B1	F/R	130/70-12	56J	19	5	33	6	8	3.50X12	TL	Y
047611278B1	F/R	130/80-12	69J	20	5	36	6	9	3.00X12	TL	Y
047611220B1	F/R	140/70-12	60J	20	6	33	6	8	3.75X12	TL	Y
047611281B1	F/R	130/60-13	53J	19	5	33	6	7	3.50X13	TL	Y
047611287B1	F/R	140/60-13	57J	20	6	33	6	8	3.75X13	TL	Y
047611606B1	F/R	100/90-16	54P	23	4	33	6	8	2.50X16	TL	Y
047611791B1	F/R	120/90-17	64H	26	5	33	10	13	2.75X17	TL	Y
047611778B1	REAR	130/80-17	65H	25	5	33	10	13	3.00X17	TL	Y
047611823B1	F/R	110/80-18	58H	25	4	33	10	12	2.50X18	TL	Y
047611879B1	F/R	120/80-18	62H	26	5	33	10	13	2.75X18	TL	Y
047611905B1	F/R	100/90-19	57H	26	4	33	8	12	2.50X19	TL	Y
047612108B1	FRONT	90/90-21	54H	27	4	33	8	11	2.15X21	TL	Y
047611607B1	FRONT	130/90-16	73H	25	5	42	7	8	3.00X16	TL	Y
047611608B1	REAR	130/90-16	73H	25	5	42	9	9	3.00X16	TL	Y
047611609B1	REAR	150/80-16	71H	26	6	42	9	9	3.50X16	TL	Y

KENDA
TRAKMASTER

DUAL SPORT



TRAKMASTER K760

- Perfect choice for the recreational trail rider requiring a DOT approved tire to connect the trails on short lengths of pavement
- Tall aggressive knobs designed for varying terrain
- Durable compound for extended tread life
- Classic design at an affordable price
- Tube type
- DOT approved
(90% dirt/10% road)



ICE TIRE K335

- Studdable design specifically for ice riding
- Hard rubber compound helps retain studs during extreme riding
- Best performance available at a great value
- Allows up to a 5/8" stud without a liner
- Tube type
- DOT approved for Street use

Pavement: N/A
Dirt & Gravel: N/A

Large ADV: N/A
Mileage: N/A

K270 DUAL SPORT

- Proven reliability and performance in the toughest conditions on Earth including the Baja 1000 and Best in the Desert Series
- Best value in the Dual Sport category
- Tube type
- 4 and 6-ply rated casings
- DOT approved
(40% dirt/60% road)



PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K760 TRAKMASTER											
047601032CO	REAR	250-10	38M	15	3	40	6	3	1.50X10	TT	Y
047601203CO	FRONT	80/100-12	50M	18	3	33	10	4	1.85X12	TT	Y
047601401CO	FRONT	60/100-14	38M	19	2	40	8	3	1.50X14	TT	Y
047601404CO	REAR	90/100-14	49M	22	4	33	14	8	1.85X14	TT	Y
047601604CO	REAR	90/100-16	58M	23	4	40	13	8	1.85X16	TT	Y
047601702CO	FRONT	70/100-17	46M	23	3	40	10	6	1.60X17	TT	Y
047601709CO	REAR	130/90-17	68M	26	6	33	16	12	3.00X17	TT	Y
047601807CO	REAR	100/100-18	59M	26	5	33	16	11	2.50X18	TT	Y
047601811CO	REAR	110/100-18	64M	27	5	33	17	12	2.50X18	TT	Y
047601813CO	REAR	120/100-18	68M	27	5	33	17	12	2.75X18	TT	Y
047601902CO	FRONT	70/100-19	42M	25	3	40	10	7	1.60X19	TT	Y
047601906CO	REAR	100/90-19	57M	26	4	33	16	10	2.15X19	TT	Y
047601910CO	REAR	110/90-19	62M	27	5	33	17	11	2.15X19	TT	Y
047601912CO	REAR	120/90-19	66M	28	5	33	17	12	2.50X19	TT	Y
047602103CO	FRONT	80/100-21	51M	27	4	33	13	9	1.60X21	TT	Y
K335 ICE TIRE											
043351850B0	REAR	400-18	64P	27	5	32	12	14	2.15X18	TT	Y
043351850C0	REAR	400-18	69P	27	5	40	12	14	2.15X18	TT	Y
043351950B0	REAR	400-19	65P	27	5	32	12	13	2.15X19	TT	Y
043351950C0	REAR	400-19	71P	27	5	40	12	14	2.15X19	TT	Y
K270 DUAL SPORT											
042701738B0	REAR	325-17	50P	24	4	33	9	7	2.15X17	TT	Y
042701760C0	F/R	460-17	65P	25	5	40	14	11	2.15X17	TT	Y
042701764C0	REAR	510-17	71P	26	5	40	15	14	3.00X17	TT	Y
042701834B0	FRONT	275-18	42P	24	3	33	7	6	1.85X18	TT	Y
042701842B0	REAR	350-18	56P	26	4	33	9	9	2.15X18	TT	Y
042701850B0	REAR	400-18	64P	26	4	33	12	11	2.15X18	TT	Y
042701852B0	REAR	410-18	58P	25	4	33	9	9	2.15X18	TT	Y
042701858C0	REAR	450-18	73P	27	5	40	16	13	2.50X18	TT	Y
042701860B0	REAR	460-18	63P	26	4	33	14	11	2.50X18	TT	Y
042701864C0	REAR	510-18	73P	27	5	40	15	15	3.00X18	TT	Y
042701805C1	REAR	100/90-18	62P	25	4	33	13	10	2.50X18	TT	Y
042701806C1	REAR	120/80-18	68P	26	5	40	14	11	2.75X18	TT	Y
042702134B0	FRONT	275-21	43P	27	3	33	7	6	1.85X21	TT	Y
042702136B0	FRONT	300-21	51P	28	3	33	10	8	1.85X21	TT	Y
042702138B0	FRONT	325-21	57P	28	4	33	9	9	2.15X21	TT	Y





INTRODUCING THE NEW KENDA KM1

KM1 KM001

- State-of-the-art construction and advanced rubber compound technology combine to create Kenda's first sport-touring radial
- Optimized apex geometry delivers perfect balance of high-speed stability and lightning fast turn-in
- Proprietary compound reaches target operating temperature faster than competitors
- Excellent wet grip and increased siping combine to provide ultimate confidence in adverse conditions
- Long-wearing compound promises more miles without sacrificing performance



PART #	FRONT/REAR	SIZE	LOAD/SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
KM1											
040017017B1	FRONT	120/70ZR17	58W	23.6	5	42	5	12	3.50X17	TL	Y
040015517B	REAR	180/55ZR17	73W	24.8	7	42	7	17	5.50X17	TL	Y
040015017B1	REAR	190/50ZR17	73W	24.8	7	42	7	18	6.00X17	TL	Y

STREET





STREET



KANINE KR20

- Designed for 3-wheel autocycle applications
- Increased mileage and better handling than competitors
- Performance pattern reduces rolling resistance while retaining maximum lateral traction
- Engineered with more siping to evacuate standing water and provide excellent wet weather performance
- MC-spec, DOT, and E-Mark approved



CATACLYSM K6702

- Dual-compound technology for improved mileage and added shoulder grip
- Efficiently disperses water while minimizing uneven wear
- Designed to roll under the largest, heaviest bikes on the market
- Tubeless construction
- DOT approved / H-rated



KRUZ K673

- Excellent choice for heavy cruisers and tourers
- One of the best values on the market, with great all-weather grip, mileage and price
- Tubeless construction
- DOT approved / H-rated

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
KR20 KANINE											
042015001A1	FRONT	165/55R15	55H	23	7	44	7	15	5.00X15	TL	Y
042015002A1	REAR	225/50R15	76H	24	9	44	8	18	7.00X15	TL	Y
K6702 CATAclySM											
046702150101	REAR	170/80B15	77H	26	7	42	7	22	4.00X15	TL	Y
046702160101	FRONT	130/90B16	67H	25	5	42	5	20	3.00X16	TL	Y
046702160201	REAR	130/90B16	73H	25	5	42	7	17	3.00X16	TL	Y
046702160301	REAR	140/90B16	77H	26	6	42	7	19	3.50X16	TL	Y
046702160401	REAR	150/80B16	77H	25	6	42	7	20	3.50X16	TL	Y
046702160501	REAR	180/65B16	81H	25	7	42	7	20	5.00X16	TL	Y
046702170101	FRONT	130/80B17	65H	25	5	42	5	16	3.00X17	TL	Y
046702170201	REAR	160/70B17	79H	26	6	42	7	21	4.50X17	TL	Y
046702180101	FRONT	130/70B18	63H	26	5	42	5	16	3.50X18	TL	Y
046702190301	FRONT	130/60B19	61H	25	5	42	5	10	3.50X19	TL	Y
046702190101	FRONT	100/90B19	57H	26	4	42	5	11	2.50X19	TL	Y
046702210101	FRONT	80/90-21	54H	27	3	42	5	9	1.85X21	TL	Y
0467022210201	FRONT	90/90-21	54H	27	4	42	5	10	2.15X21	TL	Y
0467022210301	FRONT	130/60B21	63H	27	5	42	5	11	3.50X21	TL	Y
K673 KRUZ											
046731516B1	REAR	140/90-15	70H	25	6	40	7	19	3.50X15	TL	Y
046731524B1	REAR	150/90-15	74H	26	6	40	8	21	3.50X15	TL	Y
046731526B1	REAR	170/80-15	77H	26	7	40	8	23	4.00X15	TL	Y
046731614CF	FRONT	130/90-16	72H	25	5	40	4	17	3.00X16	TL	Y
046731614C1	REAR	130/90-16	74H	25	5	40	7	18	3.00X16	TL	Y
046731616C1	REAR	140/90-16	77H	26	6	40	9	21	3.50X16	TL	Y
046731625B1F	FRONT	150/80-16	71H	25	6	40	7	17	3.50X16	TL	Y
046731625B1	REAR	150/80-16	71H	25	6	40	7	19	3.50X16	TL	Y
046731626B1	REAR	160/80-16	75H	26	6	40	9	22	4.00X16	TL	Y
046731712F1	FRONT	120/90-17	64H	26	5	40	5	15	2.75X17	TL	Y
046731782C1	FRONT	140/80-17	69H	26	6	41	5	17	3.50X17	TL	Y
046731810B1	FRONT	110/90-18	61H	26	4	40	5	11	2.50X18	TL	Y
046731812C1	FRONT	120/90-18	71H	27	5	40	5	14	2.75X18	TL	Y
046731819F1	FRONT	130/70-18	63H	25	5	40	5	15	3.50X18	TL	Y
046731905C1	FRONT	100/90-19	57H	26	4	40	5	11	2.50X19	TL	Y
046731910B1	FRONT	110/90-19	62H	27	4	40	5	12	2.50X19	TL	Y
046732176C1	FRONT	80/90-21	48H	27	3	40	3	9	1.85X21	TL	Y



KENDA
CHALLENGER III

STREET



CHALLENGER K657

- Excellent choice for middleweight sport-touring motorcycles
- Tread pattern designed for all-weather riding
- Tubeless construction
- DOT approved / H-rated

KENDA
RETROACTIVE



RETROACTIVE K676F/K676

- Sport bias belted tire for the classic bikes of the 70s, 80s and 90s
- Advanced rubber compound for improved durability and mileage
- Redesigned crown radius for larger footprint in corners
- Tubeless construction
- DOT approved / V-rated

KENDA
CRUISER



CRUISER K671

- One of the most popular choices on the market for heavy cruisers and tourers
- Deep offset tread grooves for all-weather riding
- Tubeless construction
- DOT approved / H-rated

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K657 CHALLENGER											
046571514C1	REAR	130/90-15	66H	24	5	40	6	14	3.00X15	TL	Y
046571516C1	REAR	140/90-15	70H	25	6	40	7	16	3.50X15	TL	Y
046571612C1	REAR	120/90-16	63H	25	5	40	6	12	2.75X16	TL	Y
046571618C1	FRONT	130/90-16	74H	25	5	40	6	16	3.00X16	TL	Y
046571614C1	REAR	130/90-16	74H	25	5	40	6	16	3.00X16	TL	Y
046571616C1	REAR	140/90-16	77H	26	6	40	7	17	3.50X16	TL	Y
046571714C1	REAR	130/90-17	68H	26	5	40	6	15	3.00X17	TL	Y
046571805C1	FRONT	100/90-18	56H	25	4	40	4	10	2.50X18	TL	Y
046571810C1	REAR	110/90-18	61H	26	4	40	6	12	2.50X18	TL	Y
046571812C1	REAR	120/90-18	65H	27	5	40	6	14	2.75X18	TL	Y
046571814C1	REAR	130/90-18	69H	27	5	40	6	16	3.00X18	TL	Y
046571905C1	FRONT	100/90-19	57H	26	4	40	4	10	2.50X19	TL	Y
046571910C1	FRONT	110/90-19	68H	27	4	40	4	12	2.50X19	TL	Y
046572104C1	FRONT	90/100-21	56H	28	4	40	4	12	2.15X21	TL	Y
K676 RETROACTIVE											
046761679B1	FRONT	120/80B16	60V	24	5	42	4	11	2.75X16	TL	Y
046761614B1	REAR	130/90B16	67V	25	5	42	7	16	3.00X16	TL	Y
046761627B1	REAR	150/80B16	71V	25	6	42	7	16	3.50X16	TL	Y
046761722B1	FRONT	110/70B17	54V	23	4	42	4	8	3.00X17	TL	Y
046761723B1	FRONT	110/80B17	57V	24	4	42	4	9	2.50X17	TL	Y
046761719B1	REAR	130/70B17	62V	24	5	42	7	12	3.50X17	TL	Y
046761715B1	REAR	140/80B17	69V	26	6	42	7	16	3.50X17	TL	Y
046761721B1	REAR	150/70B17	69V	25	6	42	7	16	4.25X17	TL	Y
046761805B1	FRONT	100/90B18	56V	25	4	42	4	10	2.50X17	TL	Y
046761812B1	REAR	120/90B18	65V	26	5	42	7	16	2.75X18	TL	Y
046761878B1	REAR	130/80B18	66V	26	5	42	7	16	3.00X18	TL	Y
046761905B1	FRONT	100/90B19	57V	26	4	42	4	10	2.50X19	TL	Y
K671 CRUISER											
046711514C1	REAR	130/90-15	66H	24	5	40	6	14	3.00X15	TL	Y
046711526C1	REAR	170/80-15	77H	26	7	40	7	19	4.00X15	TL	Y
046711610C1	FRONT	100/90-16	54H	23	4	40	4	10	2.50X16	TL	Y
046711622C1	FRONT	110/70-16	52P	22	4	33	5	8	3.00X16	TL	Y
046711614C1	REAR	130/90-16	74H	25	5	40	6	16	3.00X16	TL	Y
046711620C1	REAR	140/70-16	65P	24	6	33	6	11	3.75X16	TL	Y
046711772C1	FRONT	110/70-17	54H	23	4	40	4	9	3.00X17	TL	Y
046711723C1	FRONT	110/80-17	57H	24	4	40	4	11	2.50X17	TL	Y
046711719C1	REAR	130/70-17	62H	24	5	40	6	12	3.50X17	TL	Y
046711720C1	REAR	140/70-17	66H	25	6	40	6	12	3.75X17	TL	Y
046711721C1	REAR	150/70-17	69H	25	6	40	7	14	4.25X17	TL	Y
046711808C1	FRONT	90/90-18	51H	24	4	40	4	9	2.15X18	TL	Y
046711819C1	REAR	130/70-18	63H	25	5	40	6	12	3.50X18	TL	Y
046711820C1	REAR	140/70-18	67H	26	6	40	6	14	3.75X18	TL	Y
046711905C1	FRONT	100/90-19	57H	26	4	40	4	10	2.50X19	TL	Y



United Oil
INSURANCE • VALUE • RELIABILITY

SCOOTER/MINI-MOTO



KENDA
BIG
BB
BLOCK



BIG BLOCK K784

- Our famous ADV tire, now for small bore bikes
- Deep lugs help take your Honda Grom, Monkey or Kawasaki Z125 to places it's never been before
- Great wear allows for daily riding on all surfaces

KENDA
SMALL
SB
BLOCK



SMALL BLOCK K262

- Classic waffle tread pattern with offset shoulder lugs for increased stability
- 50/50 street/dirt application for confidence on all surfaces
- Perfect for smaller street and trail bikes
- DOT and E-Mark compliant

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K784 BIG BLOCK											
047841201B1	FRONT	120/70-12	51P	19	5	33	10	7	3.50X12	TL	Y
047841202B1	REAR	130/70-12	56P	19	5	33	10	9	3.50X12	TL	Y
K262 SMALL BLOCK											
042621701B0	F/R	275-17	41P	23	3	33	7	5	1.85X17	TT	Y
042621702B0	F/R	300-17	45P	24	3	33	8	7	1.85X17	TT	Y
042621703B0	F/R	325-17	50P	24	4	33	8	7	2.15X17	TT	Y
042621801B0	F/R	275-18	42P	24	3	33	7	6	1.85X18	TT	Y



SCOOTER/mini-MOTO



SCOOTER/MINI-MOTO

KWICK II KD2

- Race-optimized super sticky compound heats up quicker for immediate track performance
- Silica base provides better wet weather performance and braking in all conditions
- Lower rolling resistance combined with natural straight-line stability for faster straightaways
- All-new carcass construction translates to vastly improved lateral response and grip in the corners



KWICK KD1

- Race-inspired super sticky compound
- Enhanced water drainage and professional-level grip
- Designed for low rolling resistance and optimal cornering traction
- Ideal for Honda Grom, Monkey, Kawasaki Z125 and similar lightweight street bikes



KOZMIK K6022

- All-weather performance tread for uncompromising grip in all conditions
- Long-wearing compound provides increased mileage without sacrificing performance

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
KD2											
04KD21009012	FRONT	100/90-12	51L	19	4	25	4	7	2.50X12	TL	Y
04KD21208012	REAR	120/80-12	55J	19.6	4.7	25	4	9	2.75X12	TL	Y
KD1 KWICK											
04KD1120011	REAR	120/70-12	51L	19	5	33	4	7	3.50X12	TL	Y
04KD1120021	REAR	120/80-12	55J	20	5	25	4	9	2.75X12	TL	Y
04KD1120031	REAR	130/70-12	56L	19	5	33	4	8	3.50X12	TL	Y
04KD1F120011	FRONT	100/90-12	49J	19	4	25	4	8	2.50X12	TL	Y
04KD1F120021	FRONT	110/70-12	47L	18	4	33	4	7	3.00X12	TL	Y
04KD1F120031	FRONT	120/70-12	51L	19	5	33	4	8	3.50X12	TL	Y
K6022 KOZMIK											
04602210501	F/R	350-10	51J	17	4	36	5	6	3.00X12	TL	Y
04602212101	F/R	110/70-12	47L	18	4	33	6	7	3.00X12	TL	Y
04602212201	F/R	120/70-12	51L	18	5	33	6	8	3.50X12	TL	Y
04602212301	F/R	130/70-12	56L	19	5	33	6	9	3.50X12	TL	Y

SCOOTER/MINI-MOTO





WINTER TIRE K701

- Unique compound for cold weather traction
- Tread and sipes designed for improved traction in wintry conditions



K329

- Performance-style tread pattern
- Balanced design for both mileage and wet weather traction



K413

- Race-inspired tread pattern
- Designed for performance in all-weather conditions
- Engineered to evacuate water efficiently and maintain traction in fast corners

PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K701 WINTER TIRE											
047011035C1	F/R	300-10	47L	16	3	40	6	5	2.15X10	TL	Y
047011041C1	F/R	350-10	56L	17	4	40	6	6	2.50X10	TL	Y
047011286C1	F/R	120/70-12	58P	19	5	40	6	7	3.50X12	TL	Y
047011209C1	F/R	130/70-12	62P	19	5	40	6	8	3.50X12	TL	Y
047011381C1	F/R	130/60-13	60P	19	5	40	6	7	3.50X13	TL	Y
K329											
043291032B0	F/R	250-10	33J	15	3	33	4	8	1.50X10	TT	Y
043291034B0	F/R	275-10	37J	16	3	33	4	3	1.75X10	TT	Y
043291041B1	F/R	350-10	51J	17	4	36	6	5	2.50X10	TL	Y
043291008B1	F/R	90/90-10	50J	16	4	36	6	4	2.15X10	TL	Y
043291012B1	F/R	120/90-10	56J	19	5	25	5	12	2.75X10	TL	Y
043291016B1	F/R	140/90-10	70J	20	6	40	6	10	3.00X10	TL	Y
K413											
044131035B1	F/R	300-10	42J	16	3	36	5	7	2.15X10	TL	Y
044131041B1	F/R	350-10	51J	17	4	36	5	8	2.50X10	TL	Y
044131008B1	F/R	90/90-10	50J	16	4	36	5	12	2.15X10	TL	Y
044131024B1	F/R	100/80-10	52J	16	4	36	5	5	2.50X10	TL	Y
044131010B1	F/R	100/90-10	56J	17	4	36	5	6	2.50X10	TL	Y
044131029B1	F/R	110/80-10	58J	17	4	36	5	6	2.50X10	TL	Y
044131012B1	F/R	120/90-10	57J	19	5	25	5	8	2.75X10	TL	Y
044131009B1	F/R	130/70-10	52J	17	5	33	5	7	3.50X10	TL	Y
044131018B1	F/R	130/90-10	61J	19	5	25	5	12	3.00X10	TL	Y
044131222B1	F/R	110/70-12	47J	18	4	33	5	6	3.00X12	TL	Y
044131286B1	F/R	120/70-12	51J	19	5	33	5	7	3.50X12	TL	Y
044131209B1	F/R	130/70-12	56J	19	5	33	5	8	3.50X12	TL	Y
044131221B1	F/R	140/70-12	60J	20	6	33	5	8	3.75X12	TL	Y
044131386B1	F/R	120/70-13	53M	20	5	33	5	8	3.50X13	TL	Y
044131381B1	F/R	130/60-13	53J	19	5	33	5	7	3.50X13	TL	Y
044131387B1	F/R	140/60-13	57J	20	6	33	6	8	3.75X13	TL	Y





K433F/K434

- Performance-style tread pattern
- Sport-oriented riding tire
- Compound designed for long wear and mileage



K764

- Designed for long wear and confident grip
- Aggressive tread pattern for optimal tracking in wet or dry weather conditions



K453

- Sport tread designed with performance-based scooters in mind
- Deep grooves to evacuate standing water


PART #	FRONT/ REAR	SIZE	LOAD/ SPEED	OD INCHES	SW INCHES	MAX PSI	TREAD DEPTH - MM	WEIGHT LBS	RIM SIZE	TT/TL	DOT Y/N
K433											
044331222C1	FRONT	110/70-12	47L	18	4	33	5	6	3.00X12	TL	Y
044331223C1	FRONT	110/80-12	65J	19	4	40	5	8	2.50X12	TL	Y
044331286C1	F/R	120/70-12	58M	19	5	40	5	7	3.50X12	TL	Y
044341321B1	REAR	150/70-13	64S	21	5	33	6	13	4.25X13	TL	Y
044331486B1	FRONT	120/70-14	55S	21	5	33	5	9	3.50X14	TL	Y
044331479B1	FRONT	120/80-14	58S	22	5	33	5	10	2.75X14	TL	Y
044331586B1	FRONT	120/70-15	56S	22	5	33	5	10	3.50X15	TL	Y
044341421B1	REAR	150/70-14	66S	22	4	33	6	13	4.25X14	TL	Y
K434											
044341321B1	REAR	150/70-13	64S	21	6	33	6	13	4.25X13	TL	Y
044341421B1	REAR	150/70-14	66S	22	6	33	6	13	4.25X14	TL	Y
K764											
047641012B1	REAR	120/90-10	66M	19	5	36	5	8	2.75X10	TL	Y
047641018B1	REAR	130/90-10	61M	19	5	25	5	8	3.00X10	TL	Y
047641222C1	FRONT	110/70-12	54J	19	4	40	6	8	3.00X12	TL	Y
047641223B1	REAR	110/80-12	61J	19	4	36	5	7	2.50X12	TL	Y
047641286B1	FRONT	120/70-12	51P	19	5	33	5	12	3.50X12	TL	Y
047641209B1	REAR	130/70-12	56M	19	5	33	5	8	3.50X12	TL	Y
047641220C1	REAR	140/70-12	60M	20	6	33	5	9	3.75X12	TL	Y
047641381B1	REAR	130/60-13	53P	19	5	33	5	7	3.50X13	TL	Y
047641387B1	REAR	140/60-13	57P	20	6	33	6	8	3.75X13	TL	Y
047641486B1	FRONT	120/70-14	55P	21	5	33	5	8	3.50X14	TL	Y
047641487C1	REAR	140/60-14	64P	21	6	33	6	9	3.75X14	TL	Y
047641420B1	REAR	140/70-14	62L	22	6	33	5	10	3.75X14	TL	Y
047641738B1	REAR	325-17	50P	24	4	33	6	8	2.15X17	TL	Y
047641741B1	REAR	350-17	54P	25	4	33	7	10	2.15X17	TL	Y
047641834B1	FRONT	275-18	42P	24	3	33	5	7	1.85X18	TL	Y
K453											
044531041B1	F/R	350-10	51L	17	4	36	5	6	2.50X10	TL	Y
044531008B1	F/R	90/90-10	50L	16	4	36	5	5	2.15X10	TL	Y
044531024B1	F/R	100/80-10	53L	16	4	36	5	5	2.50X10	TL	Y
044531005B1	F/R	100/90-10	56L	17	4	36	5	6	2.50X10	TL	Y
044531023B1	F/R	110/80-10	58L	17	4	36	5	6	2.50X10	TL	Y
044531222B1	F/R	110/70-12	47L	18	4	33	5	6	3.00X12	TL	Y
044531286B1	F/R	120/70-12	51L	19	5	33	5	7	3.50X12	TL	Y
044531209B1	F/R	130/70-12	56L	19	5	33	5	8	3.50X12	TL	Y



VALVE TYPES



TR-4



TR-6



TR-13



JS-87C

MOTORCYCLE INNER TUBES

SIZE	VALVE TYPE: TR-4/TR-6	VALVE TYPE: TR-13	VALVE TYPE: TR-87/JS-87C	TUFF	SUPER TUFF
4.10/3.50-4			11041650		
4.10/3.50-5			11051650		
4.10/3.50-6			11061650		
3.00-8			11080650		
3.50-8			05081050		
4.80/4.00-8		11082230			
5.70/5.00-8		11083030			
4.00-9		11091430			
2.50/2.75-10	05103270 / 05103220		05103251	05103210T	
3.00/3.25-10	05233620 / 05103620	05103630	05103651		
3.50/4.00-10	05104220	05104230	05104251		
4.00/4.50-10	05105020	05105030	05105051		
2.50-12				05123020	
120/70-12, 130/70-12	05128020 05128050				
2.75/3.00-12	05123420				
3.00/3.25-12 (80/100-12)				05120310T	
3.25/3.50-12	05124020				
4.00/4.50-12	05125020				
2.00/2.25/2.50-14	05142820				
2.25/2.50-14 (60/100-14)				05147520T	
2.50/2.75-14	05143220				
2.75/3.00-14	05143420				
3.25/3.50-14	05143820				
3.60/4.10-14 (90/100-14)				05140410T	

MOTORCYCLE INNER TUBES


SIZE	VALVE TYPE: TR-4/TR-6	VALVE TYPE: TR-13	VALVE TYPE: TR-87/JS-87C	TUFF	SUPER TUFF
2.25/2.50-15	05153020				
2.75/3.00-15	05153420				
3.00/3.25-15 (90/90-15)	05153620			05153021	
2.00/2.25-16	05162820				
2.25/2.50-16	05163020				
2.50/2.75-16					
2.75/3.00-16	05163420				
3.00/3.25-16	05163620				
3.25/3.50-16	05164020				
90/100-16				05160420T	
4.25/4.50-16	05165420 05165420				
2.00/2.25-17	05172820 05172820				
2.25/2.50-17 (70/100-17)				05173010T	
2.50/2.75-17	05163220 05173220				
2.75/3.00-17	05173420				
3.00/3.25-17	05173620				
3.25/3.50-17	05174020				
3.75/4.25-17	05178220				
2.25/2.50-18	05183020				
2.50/2.75-18	05183220				
2.75/3.00-18	05183420				
3.00/3.25-18	05183620				
3.25/3.50-18	05184020				
3.50/4.00-18	05184220				
3.75/4.25-18	05184620				
4.00/4.50-18 (100/100-18)				05180720T	
4.50/5.10-18 (110/100-18, 120/100-18)					
5.00/5.30-18	05186220				
110/100-18				05186910T	05181110ST
120/100-18				05186910T	05181310ST
4.30/5.10-18	05188820				
2.00/2.25-19	05192820				
2.25/2.50-19 (70/100-19)	05193020			05193020T	
2.50/2.75-19	05193220				
2.75/3.00-19	05193420				
3.00/3.25-19	05193620				
3.25/3.50-19	05194020	05194030			
3.50/4.00-19 (100/90-19)					
100/90-19				05190520T	
4.00/4.50-19	05198420				
4.50/5.10-19 (110/90-19, 120/90-19)				05197420T	05191010ST
2.75/3.00-21					
3.00/3.25-21 (80/100-21)	05213620				
80/100-21				05210310T	05210310ST
3.25/3.50-21	05214020				
2.75/3.00-23	05233420				
3.00/3.25-23					



VALVE TYPES



TR-4



TR-6



TR-13



JS-87C



TR-244A

ATV INNER TUBES

SIZE	VALVE TYPE: TR-4	VALVE TYPE: TR-6	VALVE TYPE: TR-13	VALVE TYPE: TR-87/JS-87C	VALVE TYPE: TR-244A
145/70-6					11061706
16X8.00-7		11076220	11076230		
16X6.50/7.6-8		11086020	11086030		
18X7.00-8	11081910	11081930			
18X8.5/9.5-8		11086820			
18X8.5/9.5-8			11086830		
20X7.00-8		11087420			
20X10.00-8		11087620			
22X11.00-8		11088420	11088430		
20X10.00-9		11097620			
20.X12.00-9		11097720			
22X11.00-9		11098420			
25X12.00/13.00-9		11099220	11099230		
21X7.00-10		11108020			
20.50X8.00-10		11107820	11107830		
22X8.00-10		11108320			
22X11.00-10		11108420			
23.5X8.00-11		11119020			
23X8.5/10.5-12	11122120				
23X8.5/10.5-12		11122130			
24X9.00-11		11119120			
25X8.00-12		11084520			
25X10.00-12		11109520			
25/26X12-12		11129220			

TIRE SELECTION

When selecting Kenda tires for your vehicle, be sure they meet the requirements of the intended use. Make sure your tire meets your vehicle's speed requirements and load carrying capacity. Contact Kenda for more information.

FRONT/REAR TIRE MATCHING

Tires designated as front wheel fitment should only be mounted in the front position. Likewise, tires designated for rear wheel fitment should only be mounted in the rear position. Mixing new and used front and rear tires, and vice versa, can cause instability and unpredictable handling. Likewise, mixing radials and non-radials can also cause the same issues. Kenda recommends that you do not mix either of these, as it is unsafe.

TUBES

When fitting a new tire on a wheel/rim requiring a tube, a new tube should be installed at the same time. Old tubes become stretched. If an old tube is fitted within a new tire, it can crease and fail due to thinning of the tube rubber. Kenda does not recommend repairing tubes. Make sure to check the size marking on the tube to be sure it matches your tire size. Do not fit Kenda tubes in radial motorcycle tires. Contact Kenda for more information.

TIRE PRESSURES & TIRE INSPECTION

Always check your tire pressure and inspect your tires' wear for possible damage before each ride. It is by far the most important function of tire maintenance you can perform. If you add heavier loads or another passenger to your vehicle, a higher tire pressure is required. Never exceed the maximum load indicated on tire sidewall or vehicle capacity load found in the owner's manual. Underinflated tires can result in tire failure. Contact Kenda and consult your owners manual for more information.

SPEED RATINGS

Speed ratings are recognized by the Industry Standards Organization (ISO). Always match the tire speed rating to your vehicle requirement. Contact Kenda or consult your owners manual for more information.

RUN-IN PERIOD

New tires should not be subjected to maximum power or extreme cornering until the new tire has traveled at least 100 miles. This will allow the rider to get used to the feel of the tires and their performance characteristics. Remember, a new tire has different performance characteristics than a used tire of the same make/model.

TIRE REPAIR AND MODIFICATION

Kenda does not recommend repairing tires. Kenda also does not recommend the use of liquid sealants as a tire repair device. Kenda does not recommend ANY type of tire modification. Instead, faulty tires should be replaced with comparable new tires.

WHEELS AND TIRE BALANCE

It is crucial that tire and wheel assemblies are balanced properly before use. Unbalanced tire and wheel assemblies can potentially lead to tire failure. Bent or cracked wheels/rims should be replaced immediately. Contact your Kenda tire dealer to ensure proper tire and wheel installation and balancing.

LOAD CARRYING CAPACITIES

Make sure your tires have a sufficient load carrying capacity for your vehicle and added weight. When calculating your load capacity, take into account the weight of the vehicle, the weight of any additional luggage or gear, and whether you carry passengers. Proper tire inflation is necessary when making this calculation. Never exceed the vehicle load capacity noted on the Vehicle Identification Number (VIN) plate, in your vehicle owner's manual or the maximum load noted on your tires sidewall.

TIRE INSTALLATION AND MOUNTING

Kenda does not recommend installing your own tires or tubes. Contact your Kenda tire dealer to ensure proper installation and mounting.

TREAD DEPTH

Make sure to replace tires before they reach their tread wear indicator bars (1/32" tread depth remaining). Excessive tread wear can result in tire failure.



#RIDE

Through our grass roots racing and sponsorships programs, Kenda supports the racing community from all levels. On the event level, Kenda is a title sponsor for 48 series races

including the 9 race National Enduro Championship series and other favorites like the Tennessee Knockout. On the rider level, Kenda sponsors almost 800 amateur riders in it's



KENDA



annual Rider Support Program that grows each year. Kenda knows that riders like you make up the heart of the Kenda brand and we will continue to see you at the races.

KENDA



KENDA

 /kendapowersports

 /KendaTiresUSA

 /kendapowersport

 Powersports.KendaTire.com

Kenda USA Headquarters
7095 Americana Parkway
Reynoldsburg, OH 43068